

**DESCRIZIONE - DESCRIPTION**

Valvola a sfera a passaggio standard M/F  
c//premistoppa, leva in acciaio ST, e in alluminio T.

*Standard way ball valve MXF with stuffing box  
with flat steel lever and aluminium T handle.*




1130T



1130ST

**CARATTERISTICHE - FEATURES**

- corpo, manicotto e sfera, in ottone CW617N.
- Premistoppa e asta in ottone CW614N
- sfera lavorata con utensile in diamante, cromata.
- sedi in P.T.F.E. vergine.
- guarnizione tenuta asta: anello PTFE+o-r NBR
- leva di comando in acciaio plastificato ST, alluminio T
- finitura superficiale nichelata filettature gialle.
- filettature ISO 228/1
- PN 25: TEMP. : -20°C ÷ 120°C
- *brass CW617N body, bonnet and ball.*
- *brass CW614N stuffing box and stem*
- *ball ground by diamond-tipped tool, chromium plated.*
- *virgin P.T.F.E. seats.*
- *stem tightness: PTFE ring.+ o-ring in NBR rubber.*
- *Steel lever with red plastic coating ST, aluminium T*
- *Nickel plated finishing with yellow threads.*
- *threading to ISO 228/1.*
- *PN 25: TEMP. : -20°C ÷ 120°C*

**DIMENSIONI PRINCIPALI - LEADING DIMENSIONS**


R	3/8	1/2	3/4	1	1 ¼	1 ½	2
D	85	85	85	114	114	142	142
D1	54	54	54	70	70		
H	41	44	47	60	68	75	80
H1	31	34	39	49	57		
L	40.5	44.5	51	59	69	80.5	93.5
M	10.5	11	12	13	14	15.5	17
F	10	14	18	23	29	34	44

**PRESSIONI DI ESERCIZIO A MAX 80°C - WORKING PREASSURES AT 80°C**

PN 40								p.s.i. 600
PN 30								p.s.i. 435
PN 25	*	*	*	*	*	*	*	p.s.i. 350
PN 20								p.s.i. 300
	3/8"	1/2"	3/4"	1"	1 ¼"	1 ½"	2"	

**PERDITE DI CARICO - PRESSURE DROPS**

R"	3/8	1/2	3/4	1	1 ¼	1 ½	2
Kv	9	14	25.5	55.5	88	150	248

$$\Delta P [\text{mm H}_2\text{O}] = 10.000 \times \left[ \frac{G [\text{mc/h}]}{Kv} \right]^2$$